

Clear Armor Coat for Wood

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard.  
9 CFR 1910.1200. Standard must be consulted for specific  
requirements.

**U. S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved OMB No. 1210-0072

**IDENTITY (AS USED ON LABEL AND LIST)**

***Clear Armor Coat for Wood #10-18***

NOTE: BLANK SPACES ARE NOT PERMITTED. IF  
ANY ITEM IS NOT APPLICABLE, OR NO  
INFORMATION IS AVAILABLE THE SPACE MUST BE  
MARKED TO INDICATE THAT.

**SECTION I**

**MANUFACTURER NAME:**

ENVIROSAFE MANUFACTURING CORP.

**East Coast:** 7634-B Progress Cir. \* **West Coast:** 817 Benton Way  
Melbourne, FL 32904 Wenatchee, WA 98801

**CHEMTREC COMPANY CODE: C937**

**EMERGENCY PHONE NUMBER**

CHEMTREC (800) 424-9300 Domestic  
(703) 527-3887 International

**TELEPHONE NUMBER FOR INFORMATION**

1-800-800-5737

**DATE PREPARED/UPDATED**

01/09/2002 3/21/2008

D.O.T. Hazard Class: Non-Hazardous-Not Regulated

**SECTION II - Hazardous Ingredients / Identity Information**

| Hazardous Components (Specific Chemical Identity): Common Name: | OSHA PEL | ACGH TLV | Other Limits Recommended | %   |
|---|----------|----------|--------------------------|-----|
| <i>NO HAZARDOUS INGREDIENTS PRESENT</i>                         | N/A      | N/A      | NONE                     | N/A |
|   |          |          |                          |     |

N/E – Not Established

N/A – Not Applicable

**SECTION III – Physical / Chemical Characteristics**

|                          |  |   |                                 |
|--------------------------|--|---|---------------------------------|
| BOILING POINT:           | <i>N/A</i>                                   | SPECIFIC GRAVITY (H2O = 1):             | <i>1.0</i>                      |
| VAPOR PRESSURE (MM HS):  | <i>N/A</i>                                   | FREEZING POINT:                         | <i>Approx. 36<sup>0</sup> F</i> |
| VAPOR DENSITY (AIR = 1): | <i>Heavier than air</i>                      | EVAPORATION RATE ( Butyl<br>Acetate=1): | <i>Slower than<br/>ether</i>    |
| APPEARANCE AND ODOR:     | <i>Milky liquid with slight ammonia odor</i> | SOLUBILITY IN WATER:                    | <i>Soluble in water</i>         |

**SECTION IV – Fire and Explosion Hazard Data**

FLASH POINT (METHOD USED): T.C.C LEL: N/A UEL: N/A  
EXTINGUISHING MEDIA: Non-Flammable  
SPECIAL FIRE FIGHTING PROCEDURES: None  
UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: None  
FLAMMABLE LIMITS: None

**SECTION V – Reactivity Data**

STABILITY: STABLE:  X  UNSTABLE: \_\_\_\_\_  
INCOMPATIBLE (MATERIALS TO AVOID) Oxidizing agents, strong acids, alkaline material  
HAZARDOUS DECOMPOSITIONS OR BYPRODUCTS: Carbon dioxide and/or carbon monoxide  
HAZARDOUS POLYMERIZATION : MAY OCCUR \_\_\_\_\_ WILL NOT OCCUR:  X   
CONDITIONS TO AVOID: Excessive heat, poor ventilation, corrosive atmosphere, excessive aging

**SECTION VI – Health Hazard Data**

ROUTE(S) OF ENTRY: INHALATION? Yes SKIN? Yes INGESTION? Yes

HEALTH HAZARDS (ACUTE AND CHRONIC): None

Clear Armor Coat for Wood

Nasal Contact: May cause slight irritation, dizziness, fatigue, nausea and headache

Eyes: May cause slight irritation, redness and tearing on contact

Skin: May cause slight irritation, dryness and dermatitis on prolonged contact

Swallowing: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea

CARCINOGENICITY: N/A      HPT? N/A      LARC MONOGRAPHS? N/A      OSHA REGULATIONS? N/A

SIGNS AND SYMPTOMS OF EXPOSURE: Eye, Skin and Gastrointestinal irritation.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

EMERGENCY AND FIRST AID PROCEDURES:

1. EYES: Flush with clear water for 15 minutes.

2. SKIN: Wash with soap and water

3. INGESTION: Do not induce vomiting. Can cause chemical pneumonitis and pulmonary edema. Contact a physician immediately

**FOR CASES OF INGESTION OR EYE EXPOSURE, SEEK MEDICAL ATTENTION.**

**SECTION VII – Precautions for Safe Handling and Use**

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED:

1. CONTAIN SPILL, use absorbent material to take up excess and store in DOT approved container.

WASTE DISPOSAL METHOD: Dispose according to local regulations

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep container sealed when not in use.

Protect from extreme changes in temperature.

Keep product in original shipping container.

Contact local authorities for method of proper drum disposal.

Keep out of reach of children.

Read product label carefully before use.

**SECTION VIII – Control Measures**

RESPIRATORY PROTECTION: Use Adequate Ventilation

VENTILATION: LOCAL EXHAUST - YES  
MECHANICAL - N/A

SPECIAL - N/A  
OTHER - N/A

PROTECTIVE WEAR: Wear Rubber Gloves

EYE PROTECTION: Wear Face Shield or Goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear Rubber Apron or Rubber Suit.

WORK HYGIENIC PRACTICES: Handle product with caution.

**SECTION XI - TRANSPORTATION INFORMATION:**

DOT (USA) STATUS: Not regulated

TDG (CANADA) STATUS: Not regulated

AIR - INTERNATIONAL CIVIL AVIATION ORGANIZATION ICAO - ICAO STATUS: Not regulated

SEA - INTERNATIONAL MARITIME DANGEROUS GOODS (IMDG) - IMDG STATUS: Not regulated

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR RESULTS TO BE OBTAINED FROM THE USE THEREOF.

VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEETS. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSON PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN THE USE OF THIS MATERIAL.