

Elastomeric Wall Coating

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard. 9 CFR 1910.1200. Standard must be consulted for specific requirements.

U. S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1210-0072

IDENTITY (AS USED ON LABEL AND LIST)

Elastomeric Wall Coating #10-20

NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE THE SPACE MUST BE MARKED TO INDICATE THAT.

SECTION I

MANUFACTURER NAME:

ENVIROSAFE MANUFACTURING CORP.

East Coast: 7634-B Progress Cir. * **West Coast:** 817 Benton Way
Melbourne, FL 32904 Wenatchee, WA98801

CHEMTREC COMPANY CODE: C937

D.O.T. Hazard Class: Non-Hazardous-Not Regulated

EMERGENCY PHONE NUMBER

CHEMTREC (800) 424-9300 Domestic
(703) 527-3887 International

TELEPHONE NUMBER FOR INFORMATION

1-800-800-5737

DATE PREPARED/UPDATED

01/09/2002 11/03/2007

SECTION II - Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity): Common Name:	OSHA PEL	ACGH TLV	Other Limits Recommended	%
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate CAS #25265-77-4	N/A	N/A	Mm Hg @ Temp	
No toxic chemical(s) subject to reporting requirement are present			0.010 68F	0

N/E – Not Established N/A – Not Applicable

SECTION III – Physical / Chemical Characteristics

BOILING POINT:	491 deg. F	SPECIFIC GRAVITY (H2O = 1):	1.34
VAPOR PRESSURE (MM HS):	0.010	FREEZING POINT:	Approx. 32° F
VAPOR DENSITY (AIR = 1):	Heavier than air	EVAPORATION RATE (Butyl Acetate=1):	Slower than ether
APPEARANCE AND ODOR:	Thick opaque liquid, ammonia odor	SOLUBILITY IN WATER:	Soluble
COATING V.O.C.:	0.92lbs/gal-111G/ltr.		

SECTION IV – Fire and Explosion Hazard Data

FLASH POINT (METHOD USED): 214 deg. F METHOD USED: COC LEL: 0.62% UEL: 4.24%
EXTINGUISHING MEDIA: Use extinguishing suitable for surrounding fire Foam, CO2 Alcohol Foam, Dry Chemical, Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: Wear Self-contained Breathing apparatus (positive pressure demand OSHA/NIOSH Approved or equivalent and full protective gear.

UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: None

FLAMMABLE LIMITS: None

SECTION V – Reactivity Data

STABILITY: STABLE: X UNSTABLE: _____
INCOMPATIBLE (MATERIALS TO AVOID) : Oxidizing materials can cause reaction
HAZARDOUS DECOMPOSITIONS OR BYPRODUCTS: Carbon dioxide and/or carbon monoxide
HAZARDOUS POLYMERIZATION : MAY OCCUR _____ WILL NOT OCCUR: X
CONDITIONS TO AVOID: None

SECTION XII - REGULATORY INFORMATION:

This document has been prepared in accordance with the MSDS Requirements of the OSHA HAZARD COMMUNICATION STANDARD 29 CF4 1910. 1200

OSHA HAZARDOUS CHEMICAL(S): None

CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER TOXIC ENFORCEMENT ACT OF 1986):

MATERIAL(S) KNOWN TO THE STATE TO CAUSE CANCER: None materials known to the state to

Cause adverse reproductive effect: None

MASSACHUSETTS SUBSTANCE LIST: None

NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE LIST: None

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR RESULTS TO BE OBTAINED FROM THE USE THEREOF.

VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEETS. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSON PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN THE USE OF THIS MATERIAL.