



(866) 874-8070

Product Data: Easy Brick Cleaner #40-46

Product Description

A unique formulation that cleans and restores brick surfaces. Use on stucco, block, brick and brick pavers, especially red or dark colored brick.

Typical Uses

For industrial, commercial and residential use on sidewalks, driveways, buildings, floors, ramps, brick pavers, stucco, cinder block or any masonry surface that needs to be cleaned of dirt and grime.

Product Advantages

Easy Brick Cleaner is: * Fast * Easy to apply * Water clean-up * No Solvents * Will not harm or deteriorate masonry surfaces when used properly * Removes even stubborn stains * Water Soluble

Color

Clear Red

Physical Constants

Specific Gravity:
(H2O=1) 1.2 @ 24 Deg C.
Solubility in Water: Excellent
Evaporation Rate: Same as water
pH: 1.0 (Corrosive)
Storage: 40-100 deg. F



Coverage Rate

250-300 sq.ft./gal. depends on roughness of surface & degree of soil



Sold in

1-Gallon Bottles
5-Gallon Pails
55-Gallon Drums

Eco-Wares / Envirosafe Manufacturing Corp.™
East Coast: 7634-B Progress Circle, Melbourne FL 32904
West Coast: 817 Benton Way, Wenatchee, WA 98801
Phone: 866-874-8070

Web Sites
www.envirosafemfg.com
www.eco-wares.com

Products that get the job done!

EASY BRICK CLEANER #40-46

Application Instructions:

ALWAYS TEST ON SURFACES PRIOR TO APPLICATION!

SURFACE PREPARATION AND APPLICATION

NOTE: Wear gloves and goggles to protect from splashing.

1. Water all grass and shrubs well before starting. Use a Pump Sprayer to apply **EASY BRICK CLEANER**
2. Let stand for approximately 3 to 5 minutes. Length of time depends on the extent stain and the durability of the surface treated.
3. Scrub with a nylon bristle stiff broom or wire brush on any stubborn stains. Pressure wash off with minimum 3000 psi.
4. Rinse with plenty of water. Always have a water source to wash off product and equipment
5. **Clean-Up:** Clean all equipment with warm, soapy water or **Enviro-Clean Degreaser Cleaner** and water.

6. Apply **Trojan Masonry Sealer** to waterproof surface and to keep future stains from penetrating

Note: For best results use a pressure washer at a minimum of 3000 psi. We recommend you wear OSHA Compliance chemical gloves, eye protection and rubber boots for protection

Safety: Safe storage, handling and use dictate that adequate health and safety precautions be observed with this product. User is specifically directed to consult the current Material Safety Data Sheet for this product as well as precautions contained on product labeling.

Notice: The technical data contained herein are true and accurate to the best of our knowledge. All products are offered and sold subject to Envirosafe Manufacturing Corporations Standard Conditions of Sale. Published technical data and instructions are subject to change without prior notice.

LIMITATIONS

Apply in good weather when air and surface temperatures are above 45 degrees Fahrenheit and surface temperature is at least 5 degrees Fahrenheit above the dew point. For optimum application properties, materials should be between 70 to 100 degrees Fahrenheit prior to application. Maintain unused material in closed containers in protected storage at 40 - 100 degrees Fahrenheit.

Do not store material in strong sunlight

RECOMMENDED USES:

- | | | |
|------------|------------|-----------------------|
| *Walls | *Buildings | *Industrial Buildings |
| *Sidewalks | *Homes | *Commercial Buildings |
| *Driveways | *Streets | *Shopping Centers |
| *Patios | | |