

# SPECIFICATIONS

## ANTI GRAFFITI COATING #30-37

### 1. PRODUCT: ANTI-GRAFFITI COATING

### 2. MANUFACTURING AND DISTRIBUTOR:

ECO-WARES ® / ENVIROSAFE MANUFACTURING CORP. ®

**East Coast Office:** 7634-B Progress Circle  
Melbourne, FL 32904

**West Coast Office:** 817 Benton Way.  
Wenatchee, WA 98801

Web Site: [www.eco-wares.com](http://www.eco-wares.com)

Web Site: [www.envirosafemfg.com](http://www.envirosafemfg.com)

### 3. PRODUCT DESCRIPTION:

**ANTI-GRAFFITI COATING** is a special modified water-based urethane and acrylic coating that is non-hazardous and non-flammable. Good for all poured concrete, masonry surfaces, stucco, masonry block, dry-wall and brick. It is a milky and dries clear. Its special formulation provides a hard and durable gloss finish.

### 4. PRODUCT USES:

For industrial, commercial and municipal use on surfaces of masonry, brick, block and stucco on condominiums, apartments, warehouses, commercial buildings, bridges and factories.

### 5. JOB LIMITATIONS:

Apply in good weather when air and surface temperatures are above 45 deg. F. and surface temperatures is at least 5 deg. F above the Dew Point. For optimum applications properties, materials should be between 70-100 deg F. prior to application. Maintain unused material in closed containers in protected storage at 40-100 deg. F.

### 6. SURFACE PREPARATION AND APPLICATION INSTRUCTIONS:

**SPECIAL NOTE: If the surface to be coated is a painted surface, a fresh coat of paint should be applied before the ANTI-GRAFFITI COATING is applied.**

1. Prepare surface by removing loose particles, dirt, grease, oil and any biological growth. Clean with either **ENVIRO CLEAN DEGREASER CLEANER** or **NuLOOK CONCRETE CLEANER**. Rinse well and allow to dry. If the surface is very chalky, apply one coat of **TROJAN MASONRY SEALER**.
2. Apply **ANTI-GRAFFITI COATING** by brush, roller or spray equipment in a uniform manner. Allow to dry 24 Hrs. before applying second coat. Allow to cure for 72 hours.

### 7. TECHNICAL DATA:

#### PRODUCT PROPERTIES

**PHYSICAL STATE:** Milky liquid

**PH:** 8

### 8. MSDS SHEET:

AVAILABLE UPON REQUEST.

### 9. TO REMOVE GRAFFITI:

If wall is marred with graffiti, rub area to be cleaned with **ANTI-GRAFFITI CLEANER** on a rag. Then clean area with **ENVIRO CLEAN DEGREASER CLEANER**. Some graffiti may be removed with **ENVIRO CLEAN DEGREASER** alone. After several cleanings with **ANTI-GRAFFITI CLEANER** the wall surface will need to be re-coated with **ANTI-GRAFFITI COATING** to refresh and maintain the surface. **Wear chemical resistant gloves when using Anti-Graffiti Cleaner.**