

SPECIFICATIONS

ERASE CLEANER

1. PRODUCT: ERASE CLEANER:

2. MANUFACTURING AND DISTRIBUTOR:

ECO-WARES ® / ENVIROSAFE MANUFACTURING CORP. ®

East Coast Office: 7634-B Progress Circle
Melbourne, FL 32904

West Coast Office: 817 Benton Way
Wenatchee, WA 98801

Web Site: www.eco-wares.com

Web Site: www.envirosafefmg.com

3. PRODUCT DESCRIPTION:

ERASE CLEANER is a unique formulation that removes dirt, stains, oil, adhesives, some resins and paints from concrete and masonry surfaces.

4. PRODUCT USES:

For industrial, commercial and residential use on sidewalks, driveways, buildings, patios, floors and walls

5. JOB LIMITATIONS:

Apply in good weather when air and surface temperatures are above 45 degrees F. and surface temperature is at least 5 degrees F above the Dew Point. For optimum application properties, materials should be between 70-100 degrees F. prior to application. Maintain unused material in closed containers in protected storage at 40-100 degrees F. Wear gloves and goggles for personal protection. When **Erase Cleaner** is to be used under any type of coating, be certain that all traces of residue of cleaner are thoroughly removed by scrubbing or pressure washing with several rinses.

DO NOT STORE IN STRONG SUNLIGHT.

6. SURFACE PREPARATION AND APPLICATION INSTRUCTIONS:

NOTE: USE GLOVES AND GOGGLES - KEEP FROM GETTING INTO EYES.

To Remove Carpet or Vinyl Flooring Adhesives

1. Scrape all loose and excessive glue. Sweep up.
2. Spread **Erase Cleaner** by one of the following methods
 - a. Pour out and spread with a broom
 - b. Pour out and spread with a roller
 - c. Spray on with a compression sprayer
3. Allow to lay on surface for at least 1 1/2 – 2 hours or cover with polyethylene sheet and allow to sit overnight (the easiest). If it is hot or breezy you may need to mist the surface to keep it moist. If floor has a slope to it, **Erase** will have to be re-distributed from the low areas to the higher areas to re-moisten the high areas. Any vinyl floor backing that may have been left after the removal of old flooring will need to be scraped with a razor scraper after it has softened with the **Erase Cleaner**.
4. After the **Erase Cleaner** has been allowed to soften and penetrate the old adhesive, start to wire brush the softened glue. (This puts cuts and scratches in the softened adhesive and allows the **Erase Cleaner** to penetrate deeper)
5. When the **Erase Cleaner** has sufficiently softened the adhesive, you may either hose off with a strong stream or pressure wash off (the easiest and fastest)
6. Additional treatments may be required on old dried spots or extra thick areas.

7. TECHNICAL DATA:

Proprietary surfactants

pH: 10.0

8. MSDS SHEETS: AVAILABLE UPON REQUEST