

SPECIFICATIONS

ERASE CLEANER

1. PRODUCT: ERASE CLEANER:

2. MANUFACTURING AND DISTRIBUTOR:

ENVIROSAFE MANUFACTURING®/ECO-WARES, INC.
7634-B Progress Circle
Melbourne, FL 32904
Toll Free: (866) 874-8070

3. PRODUCT DESCRIPTION:

ERASE CLEANER is a unique formulation that removes dirt, stains, oil, adhesives, some paints and resins from concrete, masonry and other hard surfaces.

4. PRODUCT USES:

For industrial, commercial and residential use on sidewalks, driveways, buildings, patios, floors and Walls on surfaces of concrete, brick, stucco, block and stone.

5. JOB LIMITATIONS:

Apply in good weather when air and surface temperatures are above 45 degrees F. and surface temperature is at least 5 degrees F above the Dew Point. For optimum application properties, materials should be between 70-90 degrees F. prior to application. Maintain unused material in closed containers in protected storage at 40-90 degrees F. Wear gloves and goggles for personal protection. When **Erase Cleaner** is used prior to any type of coating, be certain that all traces of residue of **Erase** are thoroughly removed by scrubbing or pressure washing with several rinses. Do not walk on a surface that has Erase Cleaner puddled on the top-it is slippery!

DO NOT STORE IN STRONG SUNLIGHT.

6. SURFACE PREPARATION AND APPLICATION INSTRUCTIONS:

NOTE: USE GLOVES AND GOGGLES - KEEP FROM GETTING INTO EYES.

To Remove Carpet or Vinyl Flooring Adhesives

1. Scrape all loose and excessive glue. Sweep up.
2. Spread **Erase Cleaner** by one of the following methods
 - a. Pour out and spread with a broom
 - b. Pour out and spread with a roller
 - c. Spray on with a compression sprayer
3. Cover with polyethylene sheet and allow to lay on surface for at least 1 1/2 – 2 hours or best sit overnight (the easiest). If it is hot or breezy you may need to mist the surface to keep it moist. If floor has a slope to it, **Erase** will have to be re-distributed from the low areas to the higher areas to re-moisten the high areas. Any vinyl floor backing that may have been left after the removal of old flooring will need to be scraped with a razor scraper after it has softened with the **Erase Cleaner**.
4. After the **Erase Cleaner** has been allowed to soften and penetrate the old adhesive, start to wire brush the softened glue. (This puts cuts and scratches in the softened adhesive and allows the **Erase Cleaner** to penetrate deeper)
5. When the **Erase Cleaner** has sufficiently softened the adhesive, you may either hose off with a strong stream or pressure wash off (the easiest and fastest)
6. Additional treatments may be required on old dried spots or extra thick areas.

7. TECHNICAL DATA:

Proprietary surfactants
pH: 10.2

UPDATED 08/31/11